



Energy Star 5.0 Certified

Transfers heat from surrounding air to heat the water in the tank

Insulated with 3” thick CFC free polyurethane foam insulation to minimize stand-by heat loss

Thermoplastic lined tank

- User friendly electronic controller simplifies operation, maintenance, and troubleshooting
- Designed for simple installation and service by a professional plumber
- With no anode rod, maintenance is minimum
- Rebates available – check with AHRI/Energy Star websites
- Quiet application (54 dBA)
- Ducting capabilities available
- Four run modes
- Freeze protection

Energy Star rated water heating solution

The Vaughn Featherweight Heat Pump Water Heater combines the latest in heat pump technology with the proven longevity of a thermoplastic lined tank. Three inches of high quality, CFC-free foam insulation, adds to the Featherweight efficiency providing the lowest standby heat-loss rating in the industry. A streamlined user interface on the controller ensures ease of use and is highly versatile. The Vaughn Featherweight offers a low-maintenance, affordable way to take advantage of green technologies.

Applications

Residential, restaurants, schools, office buildings, and much more.



Featherweight HP Highly Efficient Heat Pump Water Heater

Available in 55, 80, & 119 Gallon Capacities

HP



FW SERIES

978-462-6683
vaughncorp.com
sales@vaughncorp.com

HEATER SPECIFICATIONS

Tank	Thermoplastic Lined
Storage	55, 80, & 119 Gallons
Orientation	Vertical
Pressure Rating:	150 psi WP, 300 psi TP
Inlet Size:	3/4" Female NPT
Outlet Size:	3/4" Male NPT
Drain Size:	3/4" GHT
Condensate Size	3/8" Tube
Relief Valve Size	3/4" Tube
Relief Valve Type	T&P, 210°F, 150 psi
Insulation:	3" Polyurethane Foam
Jacket:	High Impact Composite
Voltage:	208-240 Volt
Phase:	Single
Frequency:	60 Hz
Element:	Incoloy Sheathed
Hi-Limit	190°F Manual Reset
Thermostat Range:	50-160°F
Error Indication:	Visual and Audible
Demand Response Capable:	Yes (with option CN)
Child Lock Capable:	Yes
Refrigerant:	R134A
Ozone Depleting Potential:	0
Global Warming Potential:	1430
Over Pressure Safety:	Manual Reset
Field Chargeable:	No
Air Flow (High Fan):	450 CFM
Air Flow (Low Fan):	250 CFM
Temperature Range:	35-110°F

INSTALLATION REQUIREMENTS


- The installed location must be at least a 10' x 10' x 7' room (700 cubic feet of air space)*. If smaller, there must be a louver installed to provide sufficient airflow.
- The installed room location must not be cooler than 35°F.
- Installed locations with warmer ambient air temperature (e.g., furnace room) provide abundant “free” heat and are advantageous.
- The heat pump dehumidifies the air and as a result, produces condensate which must be piped to a drain, outdoors, or an appropriate condensate pump.
- The washable air filter requires periodic cleaning. Frequency depends upon environmental conditions.

* Additional clearance required for 119-Gal

OPTIONAL DUCTING KIT

- The ducting kit is designed to work with 10-inch diameter ducting.
- To ensure maximum performance, keep the duct as short and as straight as possible. Additionally try to make all necessary bends as wide of an angle as possible.

Example of possible ducting orientation



HOW THE VAUGHN FEATHERWEIGHT HEAT PUMP WORKS

The Featherweight Heat Pump is significantly more energy efficient than an electric water heater because the heat pump utilizes considerably less electricity. A heat pump works like a refrigerator in reverse. A refrigerator moves heat from inside the refrigerator and transfers it to the surrounding room; a heat pump water heater captures heat from the ambient air and transfers it to the tank, heating the water.


The Vaughn Featherweight Heat Pump can capture heat from air as cool as 35° F. The process of removing heat from the air and transferring it to the water results in the exhaust of cooler, dryer air. This added benefit of dehumidifying the surrounding air can provide as much as 0.4 gallons per hour of “free” dehumidification. When ducted properly, the cool air can help support the building cooling system.

If the unit cannot provide enough heating capacity to meet demand, the back-up resistive heating element will activate to ensure the unit provides sufficient hot water.

THE VAUGHN FEATHERWEIGHT HEAT PUMP STEP BY STEP OPERATION

1. The built in fan draws air from the room into the water heater heat pump compartment, across an evaporator coil, and exhausts cooler and slightly dryer (dehumidified) air.
2. The evaporator coil captures heat energy in the air and transfers that energy to a specially formulated, CFC free refrigerant contained within the evaporator.
3. The refrigerant changes from a liquid/gas mixture to 100% vapor as it gets warmer.
4. The refrigerant, now entirely vapor, exits the evaporator and passes into a compressor.
5. The vapor is compressed, causing it to become a superheated hot gas and then flows to the heat exchanger.
6. The heat exchanger transfers heat energy from the superheated hot gas to the cold water from the tank.
7. The pump circulates cold water from the tank through the heat exchanger in the upper unit, resulting in a continuous transfer of heat energy from the superheated gas to the water.
8. Hot water exits the heat exchanger and is stored in the tank.
9. The superheated gas condenses back to a liquid.
10. The liquid refrigerant expands when passing through the expansion valve, becoming a vapor/liquid mixture, and then waits to repeat the process.

HEAT PUMP OPERATIONAL DIAGRAM




SELECTABLE OPERATING MODES


Economy Mode	In the Economy Mode the heat pump provides essentially all of the heating capacity. This is typically the mode with the lowest operating cost.
Hybrid Mode	This mode optimizes both efficiency and user experience. It is the default setting. In the Hybrid Mode the heat pump provides the vast majority of the heating capacity and automatically switches to the electric resistance heater mode only when necessary to meet high demand or to optimize efficiency.
Electric Mode	The Electric Mode tells the heater to operate using only the electric resistance element and to operate like a traditional electric water heater. The heat pump is not used in this mode.
Super Mode	This mode allows both the heat pump and the electric resistance element to operate simultaneously. Due to this simultaneous operation, Super Mode provides the fastest recovery option possible.

TEMPORARY MODES

Away Mode	This mode prevents the heater from heating (regardless of what mode it is in) as a way to improve efficiency during long periods of non usage (i.e. vacation). In Away Mode the only time the heater will operate is if the unit is in danger of freezing. The user sets the number of days to be in Away Mode (adjustable from 2 to 99 days or Off), and the unit resumes its previous mode of operation at the end of this period.
Max Heat	By using the Max Heat button, you will maximize the heating capacity by temporarily putting the heater into Super Mode.
Fan Off	By using the Fan Off button, you will temporarily lower the fan speed which reduces the airflow and minimizes operating noise. Pressing the button twice temporarily disables the fan for a programmable amount of time.



DIMENSIONS



Vaughn Featherweight Dimensional Data

MODEL	A	B	C	D	E	F	G	H
	Jacket Diameter	Tank Diameter	Overall Height	Height to Hot Outlet	Height to T&P Outlet	Height to Top Thermistors	Height to Element	Height to Bottom Termistor
MP55FHPT	30	24	54.5	47.8	44	30	17	20
MP80FHPT	30	24	66.5	59.8	56	42	29	32
MP119FHPT	30	24	86	79.3	75	62	48	36

VAUGHN HP ENERGY FACTS


The Vaughn HP is designed to meet or exceed American National Standards Institute (ANSI) requirements and has been tested according to D.O.E. test procedures. It also meets or exceeds the requirements of the National Appliance Energy Conservation Act (NAECA), efficiency ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria for energy consuming appliances.

**Annual Energy Consumption Tested
at 67.5°F Ambient Air**

Model	Annual Energy Consumption kWh
MP55FHPT	982
ME55	3500
MP80FHPT	1375
ME80	5390
MP119FHPT	1418
ME119	5500

Note: Ratings are not AHRI Certified

**Amperage Rating Chart
(Amps for 4500-Watt Element)**

Supply Voltage	Total Maximum AMP Draw in Various Operating Modes			
	Economy	Hybrid	Electric	Super
240V	2.6	18.75	18.75	21.35
220V	2.8	20.45	20.45	23.25
208V	3.0	21.63	21.63	24.63

Over current circuit protection rated minimum 25 amp required, reference all local, state and national codes.

Recovery Rating (GPH) at 67.5°F Ambient Air

Recovery Capacity (Gallons per Hour for MK II Heat Pump)											
Heating Power		Water Temperature Rise (Degrees °F)									
Wattage	BTU/Hr	100	90	80	70	60	50	40	30	20	10
1,400	4,777	5.73	6.36	7.16	8.18	9.55	11.46	14.32	19.09	28.64	57.28

Heat Pump Ratings


Model	AHRI CERTIFIED					RATINGS NOT AHRI CERTIFIED		
	Nominal Capacity	Rated Storage Volume	First Hour	UEF	Usage Bin	NEEA	Sound Level	CTA
	GALLONS	GALLONS	GPH				dBa	
MP55FHPT	55	55	62	3.3	Medium	N/A	54	No
MP55FHPT-CN	55	55	62	3.3	Medium	Tier 3	54	Yes
MP80FHPT	80	80	86	3.5	High	N/A	54	No
MP80FHPT-CN	80	80	86	3.5	High	Tier 3	54	Yes
MP119FHPT	119	119	115	3.5	High	N/A	54	No
MP119FHPT-CN	119	119	115	3.5	High	Tier 3	54	Yes

THE DIFFERENCE: THERMOPLASTIC LINING

Thermoplastic lined tanks offer significant longevity, trouble-free operation and a lower lifetime cost.

Thermoplastic lining provides guaranteed 100% coverage with a minimum thickness of 0.125” Thermoplastic over all internal tank surfaces. In comparison, glass lining is approximately 0.005” thick (thickness of a single piece of paper).

- Made with polybutene and polypropylene
- Accelerated age and temperature testing = **40+ year service life**
- 100% Recyclable
- Lightweight (**<150 lbs shipping weight**)



The inner liner structure and the reinforced structure are highly compatible. During the manufacturing process both structures are fused together while molten to form a single structure called a monolithic structure.

How does Featherweight interact with water?

The two bonded layers of the Featherweight tank continuously replenish and rebalance antioxidant levels throughout the vessel over several decades of service.

Phase 1

The vessel filled with water

Phase 2


Aggressive water with oxygen attacks liner, depleting antioxidants

Phase 3

Antioxidants migrate to areas where antioxidants have been depleted

Phase 4

Antioxidants Rebalance



*Please note that this cycle as depicted above is continuous and takes place over several decades.



Vaughn is the leading manufacturer of HydraStone (HS) lined and Featherweight (FW) Thermoplastic water heaters. We manufacture 30-120 gallon electric, hybrid, indirect, and solar water heaters for residential and commercial applications as well as energy controllers and electronic devices.

To learn more, contact us

978-462-6683 | vaughncorp.com | sales@vaughncorp.com
26 Old Elm Street | P.O. Box 5431 | Salisbury, MA 01952

V1028-D-20260609