



MODEL	A	B	C	D	E	F	G	H	I	J	K	L	M	N
	Jacket Diameter	Tank Diameter	Height to Pan	Height to T&P Relief Valve	Height to Top Immersion	Height to Top HX	Height to Bottom Immersion	Height to Bottom HX	Height to Cold In	Height to Drain	Angle of T&P Relief Valve	Angle of Drain	Angle of Cold In	Angle of Immersion
65DHX62TB	26	22	46.125	39.375	38.5	31.875	17	10.875	8.375	7.875	45	45	55	55
80DHX62TB	26	22	57.125	49.875	48.875	42.5	17	10.875	8.375	7.875	45	45	55	55
80TDHX62TB	22.75	19	71.625	64.375	63.5	56.875	17	10.875	8.375	7.875	50	50	60	60
100DHX62TB	26	22	67.375	60.375	59	52.875	17	10.875	8.375	7.875	45	45	55	55
120DHX62TB	28	24	67.625	60.375	59	52.875	17	10.875	8.375	7.875	45	45	55	55

PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN INCHES
 TOLERANCES:
 LINEAR: 1 Decimal Place = ± 0.1
 2 Decimal Place = ± 0.01
 3 Decimal Place = ± 0.005
 ANGULAR: 0 Decimal Place = ± 1.0°
 1 Decimal Place = ± 0.5°
 INTERPRET GEOMETRIC TOLERANCING PER:
 MATERIAL:
 FINISH:

DRAWN	RP	DATE	6/24/2019
CHECKED	RP	DATE	4/28/2020
ENG APPR.			
MFG APPR.			
Q.A.			
COMMENTS:			
PART NUMBER:			

Vaughn Thermal Corp.
 TITLE: Tank Assembly DHX62TB Configurations
 SIZE DWG. NO. REV
C V41A0850 **C**
 SCALE: 1:8 SHEETS: 1

VAUGHN
 a nudyne company